

2

1

CABLE WALK DRAW SYSTEMS NEED ATTACHMENT POINTS CAPABLE OF 2000 LB TENSION LOAD FOR SINGLE LINE 4000 LB TENSION LOAD FOR DOUBLE LINE

OPTIONS:
BI-PART - TWO SECTIONS DRAWN TO OPPOSITE ENDS

OPTIONAL: VINYL ENCLOSED CHAIN WEIGHTED BOTTOM

1/4" CABLE
OPTION: DOUBLE LINE
(ALLOW BI-PARTED CURTAINS TO PASS BY EACH OTHER)

SNAP LINKS

MATERIAL "A"

MATERIAL "B"

HEIGHT SPECIFY

96"

STACK DEPTH

WIDTH SPECIFY

STACK DEPTH, APPROX. 1/2" PER FOOT OF CURTAIN

SPECIFY:

HEIGHT:
WIDTH:
MATERIALS:
COLORS:

SPECIFY MATERIALS

A B->	SOLID	MESH	NETTING
SOLID	X	X	X
MESH		X	X
NETTING			X

DC2518 - SPECIFICATION
DIVIDER CURTAIN - WALK
DRAWN, MESH WITH SPORTS
NETTING, CABLE

THIS PRINT IS THE PROPERTY OF GRAND SLAM SAFETY LLC AND MAY NOT BE REPRODUCED WITHOUT WRITTEN PERMISSION



(315) 301-4039
PO BOX 35
9793 BRIDGE ST.
CROGHAN, NY 13327
USA

SHEET: 1 OF 2

2

1

REV: 8/24/2017



SPECTO DIVIDER CURTAIN TO BE A MANUAL WALK DRAW, CABLE SUPPORTED CURTAIN WITH A WEIGHTED BOTTOM. THE CURTAIN SHALL COMPRISE OF THE FOLLOWING MATERIALS: SOLID 18 OZ PER SQUARE YARD SOLID VINYL COATED POLYESTER, 9 OZ PER SQUARE YARD VINYL COATED POLYESTER MESH FABRIC AND OR 1-3/4" #36 SQUARE NYLON SPORTS NETTING. MATERIALS SELF-EXTINQUISHING IN HORIZONTAL BURNING MODE.

THE ABOVE MATERIAL CAN BE USED FOR THE ENTIRE CURTAIN OR IN MULTIPLE CONFIGURATIONS, CONSULT MANUFACTURER. CUSTOMER SHALL SPECIFY COLORS.

ALL SEAMS WILL BE TRIPLE STITCHED (#69 THREAD) WITH A FULL 2" OVERLAP. EDGES WILL BE 1" TRIPLE FOLD WITH DOUBLE STITCH (#69 THREAD). A 6" SOLID VINYL STRIP SHALL BE ATTACHED TO THE BOTTOM EDGE TO FORM A POCKET TO ENCLOSE A 3/16" CHAIN FOR BALLAST. WHEN OTHER THAN SPORTS NETTING IS USED FOR THE TOP PORTION OF THE FENCE, A 6" SOLID VINYL STRIP SHALL BE ATTACHED TO THE TOP EDGE WITH #4 GROMMETS SPACED AT 18". SPORTS NETTING SHALL HAVE SEWN ROPE BORDER.

SYSTEM SHALL BE DESIGNED WITH 10% EXCESS WIDTH. OPTIONALLY THE CURTAIN CAN BE BI-PART, DESIGNED TO PART IN THE MIDDLE. ADDITIONALLY, AN OPTIONAL TWO LINE SETUP ALLOWS THE BI-PART CURTAIN SECTIONS TO PASS BY EACH OTHER IN THE MIDDLE TO ENSURE CLOSURE OF THE DIVIDER, PROVIDING MAXIMUM CONTAINMENT. SYSTEM SHALL BE DESIGNED WITH UP TO 12" EXCESS HEIGHT, ALLOWING EXCESS TO LAY ON THE GROUND TO PREVENT BALLS FROM ROLLING UNDER NET.

CABLE SHALL BE MINIMUM 1/4" GALVANIZED STEEL CABLE (6000 LBS BREAKING STRENGTH). CABLE SHALL BE ATTACHED WITH TURNBUCKLES, THIMBLES AND CLIPS. CUSTOM MOUNTING OPTIONAL, CONTACT MANUFACTURER. CUSTOMER TO SUPPLY MOUNTING POINTS CAPABLE OF MINIMUM 2000 POUND HORIZONTAL LOAD PER LINE.

THE CURTAIN SHALL BE CONNECTED TO AND SLIDE ON CABLE WITH 5/16 SPRING SNAP LINKS.

OPTIONAL 3/8 ROPE DRAW CLOSURE ALLOWING MANUAL OPERATION FROM FIELD SIDE, CONTACT MANUFACTURE.

A

A

DC2518 - SPECIFICATION
DIVIDER CURTAIN - WALK
DRAWN, MESH WITH SPORTS
NETTING, CABLE

THIS PRINT IS THE PROPERTY OF GRAND SLAM
SAFETY LLC AND MAY NOT BE REPRODUCED
WITHOUT WRITTEN PERMISSION



(315) 301-4039
PO BOX 35
9793 BRIDGE ST.
CROGHAN, NY 13327
USA

SHEET: 2 OF 2

